



CX2900-0192 battery pack

CX2900-0192 | Battery pack for CX20xx

A matching battery pack – CX2900-0192 – is available for the CX2100-0914 power supply module with integrated UPS. The CX2100-0914 module can be used to charge the external battery pack in order to provide backup power for system and external components such as Control Panels. The CX2900-0192 battery pack in metal housing can be positioned anywhere in the control cabinet on a TS35x15 2.3 DIN rail. It is continuously monitored by the CX2100-0914 charger and is therefore always optimally charged.

Technical data	CX2900-0192
Diagnostics LED	10 LEDs, illuminated
Power supply	via CX2100-0914 power supply
Capacity	3.4 Ah
Fuse	10 A
Type of connection	RJ45 socket; 3-pin socket, male
Display	–
Dimensions (W x H x D)	163 mm x 90 mm x 85 mm
Weight	approx. 2100 g
Operating/storage temperature	0...+50 °C/0...+50 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protection class	IP 20
Approvals/markings	CE

Accessories	
CX2100-0914	power supply module with integrated UPS for CX2000