



Powering Business Worldwide

pe.eaton.com

Rotary Disconnects

R5B3060U

UPC:786685402895

Dimensions:

- Height: X
- Length: X
- Width: X

Notes: Suitable as motor disconnect

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Amperage Rating:** 60A
- **Fuse Configuration:** Non-fusible
- **Number Of Poles:** Three-pole
- **Product Category:** Rotary Switch
- **Series:** R5
- **Voltage Rating:** 600V

Supporting documents:

- [Pringle Switches - Bolted contact switches](#)
- [Eatons Volume 2-Commercial Distribution](#)
- [R5B30_U AutoCAD 2D Footprint](#)
- [R5B30_U 2D Drawing Xchange](#)
- [R5B30_U 2D PDF](#)
- [R5B30_U AutoCAD 2D Footprint \(mm\)](#)
- [R5B30_U 3D Model Xchange](#)
- [R5B30_U 3D Inventor](#)
- [Eaton Specification Sheet - R5B3060U](#)

Certifications:

- IEC Rated
- EN Listed
- UL 508



- CSA Certified

Product compliance:

- CCC Marked

© 2016 Eaton. All rights reserved.