Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Modicon Momentum - Ethernet communication adaptor - 10 Mbit/s

170ENT11002



Main Range of product Modicon Momentum automation platform Ethernet TCP/IP communication adaptor Product or component type Communication port protocol Ethernet TCP/IP **Method of access** Peer to peer Master/slave 10 Mbit/s **Transmission rate** Transmission support medium Shielded twisted pairs cable Complementary Module configuration BOOTP server to assign IP parameters **Topology** Multidrop, star network **Port Ethernet** 10BASE-T Number of devices per segment 0...32 Maximum cable distance 1000 m without repeater between devices Unique IEEE global address Addressing IP address user assigned Fail state Fail safe **Control parameter** CRC-32 From I/O base Supply Marking Local signalling 1 LED (green) for Ethernet network state (LAN) 1 LED (green) for module active (RUN) **Electrical connection** 1 connector RJ45 for 10BASE-TX Net weight **Environment Product certifications** FM Class 1 Division 2 CSA **Standards** FM Class 1 Division 2

IP20

IP degree of protection

Protective treatment	TC			
Resistance to electrostatic discharge	4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2			
Resistance to electromagnetic fields	10 V/m 801000 MHz conforming to IEC 801-3			
Ambient air temperature for operation	060 °C			
Ambient air temperature for storage	-4085 °C			
Relative humidity	95 % without condensation			
Operating altitude	<= 5000 m			
Packing Units				
Unit Type of Package 1	PCE			
Number of Units in Package 1	1			

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	278.0 g
Package 1 Height	5.4 cm
Package 1 width	17.9 cm
Package 1 Length	26 cm
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Weight	2.665 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

REACh Regulation REACh Declaration			
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration		
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		

Contractual warranty

Warranty	18 months	
varianty	TO INIONAIO	