



Main

| | |
|---------------------|--|
| Range | Thalassa |
| Product name | Thalassa TBS |
| Device application | Multi-purpose |
| Category | Industrial box |
| Height | 241 mm |
| Width | 194 mm |
| Depth | 87 mm |
| Internal height | 225 mm |
| Internal width | 175 mm |
| Internal depth | 80 mm |
| Enclosure mounting | Wall mounted |
| Device composition | 1 x body 1 x cover 4 x cover screw |
| Body type | One piece moulded |
| Type of front cover | Low transparent cover |
| Cover fixing | Plastic screws |
| Lock type | Outside sealed area : flat screwdriver captive screw |
| Removable parts | Cover, by captive screws |

Complementary

| | |
|-----------------------------|---------------------------------------|
| Material | ABS (acrylonitrile butadiene-styrene) |
| Colour | Grey (RAL 7035) Transparent |
| Standards | IEC 62208 |
| Product certifications | DEMKO SEMKO TÜV |
| Electrical insulation class | Class II |

| | |
|-------------------------------------|-------------------------------------|
| IP degree of protection | IP66 conforming to NEMA 4.4X |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Fire resistance | 650 °C conforming to IEC 60695-2-11 |
| Ambient air temperature for storage | -15...40 °C |
| Operating temperature | -25...60 °C |
| Product weight | 0.64 kg |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|---------------------|
| Warranty period | 18 months 18 months |
|-----------------|---------------------|