




| Function: | | Key withdrawable in position | | Bezel: Silver | Price See price list | Std. pack | Bezel: black | Price See price list | Std. pack |
|---|------------|------------------------------|---|----------------------|--|------------|---|----------------------|-----------|
| ▷ = Momentary ▽ = Maintained | | | | Part no. Article no. | | | Part no. Article no. | | |
| Key-operated buttons for individual lock mechanisms, IP66. ATEX (Ex) → Engineering Bezel gold-plated → Page 2/48 Not suitable for master key systems With 1 key Convertible maintained/momentary function and key withdraw → Page 2/23  | | | | | | | | | |
| Two positions | | | | | | | | | |
| Lock mechanism MS1 | ▷ 40° | – | 0 | – | M22-WS 216881 | 1 off | M22S-WS 216882 | | 1 off |
| | ▽ 60° | – | 0 | I | M22-WRS 216887 | 5 off | M22S-WRS 216889 | | 5 off |
| | ▽ 60° | – | 0 | I | M22-WRS-GVP 216888 | 25 off | | | |
| | ▽ 60° | – | 0 | – | M22-WRS-A1 229092 | 5 off | M22S-WRS-A1 229093 | | 5 off |
| Lock mechanism MS2 – MS20 (Lock mechanism number in the type designation) | ▷ 40° | – | 0 | – | M22-WS-MS*1) 216883 | 1 off | M22S-WS-MS*1) 216884 | | 1 off |
| | ▽ 60° | – | 0 | I | M22-WRS-MS*1) 216890 | 1 off | M22S-WRS-MS*1) 216891 | | 1 off |
| | ▽ 50° | – | 0 | – | M22-WRS-MS*-A1¹⁾ 217440 | 5 off | M22S-WRS-MS*-A1¹⁾ 217441 | | 5 off |
| 3 positions (with plunger bridge → Engineering) | | | | | | | | | |
| Lock mechanism MS1 | 40° ↙↘ 40° | – | 0 | – | M22-WS3 216894 | 1 off | M22S-WS3 216895 | | 1 off |
| | 60° ↙↘ 60° | I | 0 | II | M22-WRS3 216900 | 5 off | M22S-WRS3 216901 | | 5 off |
| | 60° ↙↘ 60° | I | 0 | II | M22-WRS3-GVP 216902 | 25 off | | | |
| | ↙↘ | Selectable ²⁾ | – | – | M22-WRS3-A*1⁴⁾ 229094 | 5 off | M22S-WRS3-A*1⁴⁾ 229095 | | 5 off |
| Lock mechanism MS1 – MS20 (Lock mechanism number in the type designation) | Selectable | Selectable ²⁾ | – | – | M22-WRS3-MS*-A*1²⁾ 217442 | 5 off | M22S-WRS3-MS*-A*1²⁾ 217443 | | 5 off |
| | 40° ↙↘ 40° | – | 0 | – | M22-WS3-MS*1) 216896 | 1 off | M22S-WS3-MS*1) 216897 | | 1 off |
| | 60° ↙↘ 60° | I | 0 | II | M22-WRS3-MS*1) 216903 | 1 off | M22S-WRS3-MS*1) 216904 | | 1 off |
| 2 or 3 positions | | | | | | | | | |
| Lock mechanism MS1 – MS20 (Lock mechanism number in the type designation) | Selectable | Selectable | – | – | M22-WRS*-MS*-.*1³⁾ 262521 | 1 off | | | |

Information relevant for export to North America



Product Standards IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking
 UL File No. E29184
 UL CCN NKCR
 CSA File No. 012528
 CSA Class No. 3211-03
 NA Certification UL Listed, CSA certified
 Degree of Protection UL/CSA Type 3R, 4X, 12, 13