



Main

Commercial Status	Commercialised
Range	Acti 9
Product or component type	Shunt trip release
Device short name	IMX
Control circuit voltage	130 V DC 110 V DC 415 V AC 50/60 Hz 100 V AC 50/60 Hz 230 V AC 50/60 Hz
9 mm pitches	2
Product compatibility	IC60 IID Single terminal Double terminal ISW-NA IDPN Vigì ARA RCA

Complementary

Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal 1 cable(s) 4 mm² flexible Clamp terminal 2 cable(s) 2.5 mm² rigid Clamp terminal 1 cable(s) 6 mm² rigid Clamp terminal 2 cable(s) 2.5 mm² flexible with cable end
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1216 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - go to CaP for more details
Product end of life instructions	Need no specific recycling operations