# Product data sheet Characteristics

# 990NAD21110

Modbus Plus drop cable - between Momentum I/ O sub-base and T- junction - 2.4 m



-1	١,	п	9		r
-1	v	ı	а	н	ш

Accessory / separate part category	Connection accessories	<u></u>
Accessory / separate part type	Drop connection cable	er ab
Accessory / separate part designation	Modbus Plus drop cable	lc us
Accessory / separate part destination	Modbus Plus network	speci

#### Complementary

Complementary		
Product compatibility	STBNMP2212	
	990NAD23010	
	990NAD23020	
	990NAD23000	
	990NAD23021	
	140CPU43412U	
	140CPU31110	
	490NRP25300	
	NWBP85002	
Range compatibility	Modicon Momentum automation platform	
	Modicon Quantum automation platform	
	Advantys STB distributed I/O solutions	
	Modicon Premium automation platform	
	Lexium 15	
Cable length	2.4 m	
Electrical connection	1 male connector SUB-D 9 elbowed communication module side	
	Free end local site tap side	
Net weight	0.169 kg	
	<u> </u>	

## Packing Units

3 - 3		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	160 g	
Package 1 Height	2.3 cm	
Package 1 width	22 cm	
Package 1 Length	22.5 cm	
Unit Type of Package 2	S03	
Number of Units in Package 2	48	

Package 2 Weight	8.5 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

## Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

#### Contractual warranty

Warranty	18 months