

MCCB Panel Boards

800A Form 3a 50kA for 1 second

Loadbank 250
800A MCCB

Panel Boards, Outgoing
devices up to 250A

Panel Boards

- ASTA certified busbars rated at 50kA for 1 second
- Form 3a as standard
- Width is 750mm and depth is 200mm. Height as per the table below.
- Supplied with top plate and two side plates as standard
- Ingress protection of IP3X. IP4X with door kit fitted (available as optional extra)

Outgoing Triple Pole Ways	Modular Height	Height (mm)	Weight (kg)	Panel Board Product Code	Door Kit Product Code
6	4	609	42	LB806YA3	LBDD06
12	6	914	62	LB812YA3	LBDD12
18	8	1219	78	LB818YA3	LBDD18

Add-on Incoming Device Enclosures

- Supplied with all necessary copper connections
- Incoming device and neutral link to be ordered separately

Current Rating (A)	Modular Height	Height (mm)	Weight (kg)	Incoming Device Type	Product Code
400/630	5	762	45	YA6 frame MCCB	LB1YA6
800	3	457	23	Direct Connection	LBDR8
800	6	912	69	YA7 frame MCCB	LB1YA7

Incoming Device Options

Current Rating (A)	No of Poles	Device Type	Product Code	Enclosure required
400	3	Switch disconnecter	YA6B3P400D	LB1YA6
630	3	50kA MCCB	YA6H3P630T	LB1YA6
630*	3	Switch disconnecter	YA6B3P800D	LB1YA6
400	4	Switch disconnecter	YA6B4P400D	LB1YA6
630	4	50kA MCCB	YA6H4P630T	LB1YA6
630*	4	Switch disconnecter	YA6B4P800D	LB1YA6
800	3	50kA Electronic MCCB	YA7H3P800E	LB1YA7
800	3	Switch disconnecter	YA7B3P800D	LB1YA7
800	4	50kA Electronic MCCB	YA7H4P800E	LB1YA7
800	4	Switch disconnecter	YA7B4P800D	LB1YA7

* Switch Disconnecter rating when installed in LB1YA6

Panel Board Accessories

Description	Product Code
3 pole blanking plate	LBPP3PYA3
Spare End Plate	LGES
Cylinder Door Lock	DBXCL
Padlocking Door Kit	DBXPL
Panel board stacking kit	LBCK8
Busbar extension terminals for top entry panelboards	LBSKE

Twin YA5 Outgoing Housing (not designed for use with Form 4 panel boards)

- Can be mounted direct to incoming enclosure without connection kit
- When mounting to 800A panelboard connection kits are required (LBSKE and LBCK8)
- Cableway extension enclosures are necessary to assist with cabling
- Devices to be ordered separately
- Optional outgoing terminal shroud YA5TS3P for spread extensions YA5XT3P if required (1 per MCCB)
- YA5 MCCB busbar terminal cover not required, however if internal degree of protection required is greater than IP2X then terminal cover YA5TC3P required (1 per MCCB)

Description	Modular Height	Height (mm)	Weight (kg)	Product Code	Door Kit Product Code
Twin YA5 (400A max each)	3	456	35	LB802YA5	LBDD02
Castell Kit (Excl. locks)				LB802CLK	
Castell Lock Type K Series Form 1, 6-4mm bolt protrusion					

