

PRODUCT-DETAILS

416MPR6

Switched interlocked socket-outlet with RCD, 6h, 30mA, 16A, IP44, 3P+N+E



General Information

Extended Product Type	416MPR6
Product ID	2CMA167772R1000
EAN	7392696677721
Catalog Description	Switched interlocked socket-outlet with RCD, 6h, 30mA, 16A, IP44, 3P+N+E
Long Description	Switched Interlocked Socket Outlet with RCD, earthing sleeve position 6h, 30mA, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Ordering

E-Number (Sweden)	E2416888
E-Number (Finland)	2421461
E-Number (Norway)	2416888
EAN	7392696677721
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	130 mm
Product Net Height	183 mm

Product Net Length	357 mm
Product Net Depth / Length	357 mm
Product Net Weight	1.76 kg

Container Information

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	1.76 kg
Package Level 1 EAN	7392696677721
Package Level 1 Units	box 1 piece
Package Level 2 Units	45 piece

Technical UL/CSA

Ampere Rating UL/CSA	20 A
Tightening Torque UL/CSA	7.1 in-lb

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1507476
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Cable Diameter	13 ... 17 mm
Cable Entry Position	Top
Cable Outlets Per Side	2xØ25
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Enclosure Material	Thermoplastic polyester (PBT)
Frequency (f)	50 Hz 60 Hz
Function	Switched interlocked socket outlet with RCD, 30 mA
Housing Material	Thermoplastic (PBT)

Invoice Description	Ind. P&S#416MPR6
Material	Plastic
Mounting Holes	290x100
Mounting Type	Vertical
Number of Poles	5
Number of RCDs 30mA	1
Number of RCDs	1
Order Multiple	1 piece
Product Main Type	CMPR
Product Name	Industrial Switched Interlocked Socket Outlet
Protection Type	RCD
Rated Current (I_n)	16 A
Rated Residual Current	30 mA
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	IEC 60309-1, -2, -4
Sub-Function	Cable entry, knock-outs 2xØ25mm
Suitable For	Switched Interlocked Socket Outlets with RCD
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000041M0001
Installation Manual	2CMC000041M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets with RCD

