

T4L 250 PR221DS-I In=250 4p F FC 1000VAC

T4L 250 PR221DS-I In=250 4p F FC 1000VAC



General Information

Extended Product Type	T4L 250 PR221DS-I In=250 4p F FC 1000VAC
Product ID	1SDA063423R1
EAN	8015644660420
Catalog Description	T4L 250 PR221DS-I In=250 4p F FC 1000VAC
Long Description	C.BREAKER Tmax T4L 250 1000V AC FIXED FOUR-POLE WITH FRONT TERMINALS FOR CABLE Cu AND SOLID-STATE RELEASE IN AC PR221DS-I R 250

Ordering

EAN	8015644660420
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Weight	1 kg
--------------------	------

Container Information

Package Level 1 Units	1 piece
Package Level 1 EAN	8015644660420

Additional Information

Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 10.7 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	Main Circuit 250 A
Rated Operational Voltage	1000 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(1000 V AC) 12 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(415 V AC) 120 kA (1000 V AC) 12 kA
Rated Uninterrupted Current (I_u)	250 A

Release Type	EL
Standards	IEC 60947
Sub-type	T4
Terminal Connection Type	Fixed Circuit-Breakers Front for Copper Cables
Version	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SDC210023D0201
Declaration of Conformity - CE	1SDL000165R0004
GL Certificate	1SDL000163R0061
Instructions and Manuals	1SDC210033D0202

Classifications

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

