

T7L 1200 UL PR332/P LSI In1200A 4p FF



T7L 1200 UL PR332/P LSI In1200A 4p FF

General Information

Extended Product Type	T7L 1200 UL PR332/P LSI In1200A 4p FF
Product ID	1SDA065302R1
EAN	8015644681142
Catalog Description	T7L 1200 UL PR332/P LSI In1200A 4p FF
Long Description	C.BREAKER Tmax T7L 1200 UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC PR332/P-LSI R 1200

Ordering

EAN	8015644681142
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	280 mm
Product Net Height	268 mm
Product Net Depth / Length	154 mm
Product Net Weight	12.5 kg

Container Information

Package Level 1 EAN	8015644681142
---------------------	---------------

Additional Information

Mechanical Durability	10000 cycle 60 cycles per hour
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 47 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	Main Circuit 1200 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV 1000 V

Rated Insulation Voltage (U_i)	
Rated Operational Voltage	630 V AC
Rated Uninterrupted Current (I_u)	1200 A
Release Type	EL
Standards	UL
Sub-type	T7
Suitable For	T7
Suitable for Product Class	Moulded Case Circuit Breakers
Terminal Connection Type	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test})	3500 V
Version	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK105713A5947
Declaration of Conformity - CE	1SDL000165R0007
Instructions and Manuals	1SDC210023D0201

Classifications

ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

