

Features

- Available with custom sound configurations
- Input overload and reverse current protection
- Automatic synchronisation with systems operation
- FM approval

Assembly**Technical data****Electrical specifications**


Operating voltage	16 ... 28 V DC , via zener barrier or galvanic isolator
Operating current	25 mA @ 24 V via 28 V 300 Ω zener barrier
Terminal capacity	0.5 ... 2.5 mm ²
Function	alarm sounder
Sound pressure level, nominal	100 dB @ 1 m +/- 3 dB - sound 2 , 91 dB @ 3 m
Sound pressure level, control	90 ... 100 dB , sound 2
Effective sound range	40 m @ 1 kHz
Number of sounds	32 , UKOOA / PFEER compliant
Number of stages	3

Mechanical specifications

Degree of protection	IP65
Cable entry face A	
M20 quantity	1
M20 type	thru-holes
M20 info	Stopping Plug 1x plastic
Cable entry face B	
M20 quantity	1
M20 type	thru-holes
Material	
Enclosure	fiber reinforced ABS, UL94-V0 and 5VA
Finish	RAL 3000 (red)
Mounting bracket	stainless steel 1.4301 / AISI 304
Mass	0.75 kg
Dimensions	
External dimension (A)	85.5 mm
External dimension (B)	88.7 mm

External dimension (C)	99 mm
Mounting holes distance (H)	50 mm
Mounting holes distance (H1)	60 mm
Mounting holes diameter (J)	5 mm
Maximum external dimension (K)	95 mm
Ambient conditions	
Ambient temperature	-40 ... 60 °C (-40 ... 140 °F)
Storage temperature	-40 ... 70 °C (-40 ... 158 °F)
Data for application in connection with hazardous areas	
EU-type examination certificate	SIRA 05 ATEX 2084X
Marking	Ex II 1 G Ex ia IIC T* Ga , T4 @ Ta +60 °C
International approvals	
FM approval	
Approved for	Class I, Division 1, Groups A, B, C, D, T4 Class I, Zone 0, AEx ia IIC T4
IECEx approval	IECEx SIR 06.0045X
EAC approval	RU C-GB.MH04.B.00048
Conformity	
Degree of protection	EN 60529
General information	
Scope of delivery	device , Instruction leaflet
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperl-fuchs.com .

Dimensions



Legend

A	Height
B	Width
C	Depth
G	Mounting holes distance
H	Mounting holes distance
H1	Mounting holes distance from edge of bracket
J	Mounting holes diameter
K	Maximum outer dimension with bracket
K1	Maximum outer dimension with horn
S	Depth of mounting bracket
[A] ... [B]	Cable entry faces

Dimension values see technical data table.

Image and drawing are generic for this device type and may deviate from the specific variant.

Release date 2020-01-21 15:30 Date of issue 2020-01-21 t191128_eng.xml