



Representative Image

**Ref. No. 109466 | Cat. No. CL04A310M6**

**Description: CL04A310M6 Contactor 3-pole 230V 50/60Hz**

**EAN 8425095094666**

**Home > Power devices > Contactors > 4. Series CL: Contactor for general purpose application 9-105A AC3**

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 230 VAC Max.oper.current AC1 (A): 60 Max.oper.current AC3 (A): 32 Admissible power 220V/230V (kW): 9 Admissible power 380V/400V (kW): 16 Aux.contacts: 1NO

**Descriptors**

Category	4. Series CL: Contactor for general purpose application 9-105A AC3
----------	--

**Specifications**

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Terminal type	Double clamp terminal
Max. operating current AC1 Non-inductive loads	60 A
Max. operating current AC3 Motors = 480V, 3-phase 50/60Hz	32 A
Electrical endurance: # operations AC3	2 x 10 <sup>6</sup>
Aux Contacts	1NO
Type	For contactors type CL - D
Control Voltage: AC (50/60 Hz)	220-230 V
Admissible power AC3 220V, 230V	9 kW
Admissible power AC3 380V, 400V	16 kW
Admissible power AC3 415V, 440V	16 kW
Admissible power AC3 500V	18.5 kW
Package (pcs)	10
Utilization Category	AC3
Number of main poles	3 poles
Class	1. Contactors

**Classifications**

ETIM 5.0	EC000066
ETIM 6.0	EC000066

**Dimensions**

Weight	0.520 kg
--------	----------

## Publications

Title	Publication No.	Publication Type
<a href="#">4-pole CL03A-CL04A (stp)</a>		
4-pole CL03A-CL04A (STEP format)	3D-00017	Drawings - CAD - 3D
<a href="#">4-pole CL03A-CL04A (pdf)</a>		
4-pole CL03A-CL04A (3DPDF format)	3D-00017-PDF	Drawings - CAD - 3D

**Additional Documentation:** Visit our Publication Library to find technical documentation, specifications, catalogues, promotional literature, 3D's,...