

T6H800 MCP-UL/CSA PR221DS-I

In=800 3p FF



T6H800 MCP-UL/CSA PR221DS-I In=800 3p FF

General Information

Extended Product Type	T6H800 MCP-UL/CSA PR221DS-I In=800 3p FF
Product ID	1SDA061708R1
EAN	8015644642471
Catalog Description	T6H800 MCP-UL/CSA PR221DS-I In=800 3p FF
Long Description	C.BREAKER TMAX T6H 800 MCP UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND MAGNETIC RELEASE IN AC PR221DS-I Iu 800 A

Ordering

EAN	8015644642471
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	210 mm
Product Net Height	268 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	9.5 kg

Container Information

Package Level 1 EAN	8015644642471
---------------------	---------------

Additional Information

Mechanical Durability	20000 cycle 120 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 21 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	Main Circuit 800 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV 1000 V

Rated Insulation Voltage (U_i)

Rated Operational Voltage	600 V AC
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(240 V AC) 200 kA (480 V AC) 65 kA (600 V AC) 35 kA (500 V DC) 2 Poles in Series 50 kA (600 V DC) 3 Poles in Series 35 kA
Rated Uninterrupted Current (I_u)	800 A
Release Type	EL
Standards	UL
Sub-type	T6
Suitable For	T6
Suitable for Product Class	Moulded Case Circuit Breakers
Terminal Connection Type	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test})	3500 V
Version	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK105713A5947
Declaration of Conformity - CE	1SDL000165R0006
Instructions and Manuals	1SDC210023D0201

Classifications

ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

