

432ERU7W



Panel mounted socket outlets, 3P+N+E, 32A, 277/480 ... 288/500 V



General Information

Extended Product Type	432ERU7W
Product ID	2CMA101320R1000
EAN	7392696013208
Catalog Description	Panel mounted socket outlets, 3P+N+E, 32A, 277/480 ... 288/500 V
Long Description	Panel mounted socket outlet, 3P+N+E, 32A, 277/480 ... 288/500 V Clock Position Of Grounding Contact 7 hour Color code Black

Ordering

EAN	7392696013208
Minimum Order Quantity	10 piece
Country of Origin	Czech Republic (CZ)

Dimensions

Product Net Width	85 mm
Product Net Height	104 mm
Product Net Length	101 mm
Product Net Depth / Length	101 mm
Product Net Weight	0.23 kg

Container Information

Package Level 1 Width	94 mm
Package Level 1 Depth / Length	192 mm
Package Level 1 Height	442 mm
Package Level 1 Gross Weight	2.3 kg
Package Level 1 EAN	7392696022026
Package Level 1 Units	box 10 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001_G
Declaration	2CMC700005D0001_G
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001_G

SEMKO Certificate

1616295

Additional Information

Additional Information	3P+N+E
Cable Cross-Section	2.5 ... 6 mm ²
Color	Black
Connection Type	Screw Clamp
Degree of Protection	IP67
Enclosure Material	Plastic (PA)
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#432ERU7W
Mounting Holes	75x75
Mounting Type	Unified straight flange
Number of Poles	5
Order Multiple	10 piece
Product Main Type	ERU
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current (I _n)	32 A
Rated Voltage (U _r)	277/480 ... 288/500 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1 IEC 60309-2

Classifications

eClass	27440504
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

