

E1N-A 800 PR122/P-LSIG In=800A 3p W MP



E1N-A 800 PR122/P-LSIG In=800A 3p W MP

General Information

| | |
|-----------------------|---|
| Extended Product Type | E1N-A 800 PR122/P-LSIG In=800A 3p W MP |
| Product ID | 1SDA060937R1 |
| EAN | 8015644634605 |
| Catalog Description | E1N-A 800 PR122/P-LSIG In=800A 3p W MP |
| Long Description | SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E1N-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSIG R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

Ordering

| | |
|------------------------|---------------|
| EAN | 8015644634605 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 324 mm |
| Product Net Height | 461 mm |
| Product Net Depth / Length | 396.5 mm |
| Product Net Weight | 44 kg |

Container Information

| | |
|---------------------|---------------|
| Package Level 1 EAN | 8015644609139 |
|---------------------|---------------|

Additional Information

| | |
|-----------------------|---|
| Current Type | AC |
| Electrical Durability | Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour |
| Mechanical Durability | 20000 cycle 30 cycles per hour |
| Number of Poles | 3 |
| Power Loss | at Rated Operating Conditions per Pole 95 W |
| Product Main Type | SACE Emax |
| Product Name | Air Circuit Breaker |

| | |
|---|--|
| Product Type | CBMP |
| Rated Current (I_n) | 800 A |
| Rated Voltage (U_r) | 600 V |
| Rated Operational Current (I_e) | 800 A |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) | (240 V AC) 50 kA (480 V AC) 50 kA (600 V AC) 50 kA |
| Rated Uninterrupted Current (I_u) | 800 A |
| Release Type | EL |
| Standards | UL 1066 |
| Sub-type | E1 |
| Terminal Connection Type | Withdrawable Circuit-Breakers |
| Version | W |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC200008D0202 |
| Declaration of Conformity - CE | 1SDL000165R0013 |
| Instructions and Manuals | 1SDH000532R0002 |

Classifications

| | |
|---------------|---|
| ETIM 4 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 5 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 6 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

