

DS201 M B13 AC30



DS201 M B13 AC30 - RCBO



General Information

| | |
|-----------------------|---|
| Extended Product Type | DS201 M B13 AC30 |
| Product ID | 2CSR275040R1135 |
| EAN | 8012542999102 |
| Catalog Description | DS201 M B13 AC30 - RCBO |
| Long Description | The DS201 series RCBO is a 1P+N in two-modules device for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA). |

Ordering

| | |
|------------------------------|-----------------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85363010 |
| Replacement Product ID (NEW) | 2CSR275080R1135 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CSC400002D0209 |
| Instructions and Manuals | 9AKK106354A0766 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 0.035 m |
| Product Net Height | 0.085 m |
| Product Net Depth / Length | 0.069 m |
| Product Net Weight | 0.239 kg |

Technical

| | |
|--------------------------|--|
| Standards | IEC 61009-1 IEC 61009-2-1 EN 61009-1 EN 61009-2-1 |
| Type of Residual Current | AC type |
| Rated Residual Current | 30 mA |
| Tripping Characteristic | B |
| Rated Current (I_n) | 13 A |

| | |
|---|------------------------|
| Number of Poles | 1+N |
| Number of Protected Poles | 1 |
| Rated Short-Circuit Capacity (I_{cn}) | (230 / 400 V AC) 10 kA |
| Position of Neutral Terminals | Right |
| Power Loss | 2.2 W |
| Rated Voltage (U_r) | 230-240 V AC |

Environmental

| | |
|-------------------------|--|
| Ambient Air Temperature | Operation -25 ... +55 °C Storage -40 ... +70 °C |
| RoHS Status | Following EU Directive 2011/65/EU |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|---------------------------|
| Declaration of Conformity - CE | 9AKK106713A5588 |
| Environmental Information | refer to RoHS information |
| Instructions and Manuals | 9AKK106354A0766 |
| RoHS Information | 2CSC422002K2701 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 5 piece |
| Package Level 1 Width | 0.253 m |
| Package Level 1 Height | 0.088 m |
| Package Level 1 Depth / Length | 0.108 m |
| Package Level 1 Gross Weight | 1.446 kg |
| Package Level 1 EAN | 8012542999119 |

Classifications

| | |
|----------------------------|--|
| Object Classification Code | Q |
| ETIM 4 | EC000905 - Earth leakage circuit breaker |
| ETIM 5 | EC000905 - Earth leakage circuit breaker |
| ETIM 6 | EC000905 - Earth leakage circuit breaker |
| ETIM 7 | EC000905 - Earth leakage circuit breaker |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Circuit Breakers with Overcurrent Protection RCBO

