

General Information

Extended Product Type:	HK-20
Product ID:	1SAM101901R0002
EAN:	4013614139642
Catalog Description:	HK-20 Auxiliary Contact
Long Description:	HK-20 Aux.-contact 2NO

Additional Information

Accessory Type:	Auxiliary Contact
Ambient Air Temperature:	Operation -25 ... +50 °C Storage -50 ... +80 °C
CCC Certificate:	1SAA918001-3802
Connecting Capacity Auxiliary Circuit UL/CSA:	Flexible 1/2x 14-8 AWG Stranded 1/2x 14-18 AWG
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 mm ² Flexible 1/2x 0.75 ... 1 mm ² Rigid 1/2x 1.0 ... 2.5 mm ²
Contact Rating UL/CSA:	B300 Q300
Country of Origin:	Bulgaria (BG)
Customs Tariff Number:	85369095
Data Sheet, Technical Information:	1SBC100173C0201
Declaration of Conformity - CE:	1SAD938507-0037 1SAD938514-0003 1SAD938513-0003
Degree of Protection:	IP20
E-number:	3111372
EAN:	4013614139642
ETIM 4:	EC002498 - Accessories for low-voltage switch technology
ETIM 5:	EC000041 - Auxiliary contact block
ETIM 6:	EC000041 - Auxiliary contact block
GOST Certificate:	1SAA918000-2703
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SAM107008P0002
Invoice Description:	HK-20 Aux.-contact 2NO
Minimum Order Quantity:	1 piece
Number of Auxiliary Contacts NC:	0
Number of Auxiliary Contacts NO:	2
Object Classification Code:	Q
Package Level 1 EAN:	4013614442322
Package Level 1 Gross Weight:	0.365 kg
Package Level 1 Height:	105 mm
Package Level 1 Length:	79 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	210 mm

Product Main Type:	HK
Product Name:	Auxiliary Contact
Product Net Depth:	72 mm
Product Net Height:	86 mm
Product Net Weight:	0.03 kg
Product Net Width:	9 mm
Rated Frequency (f):	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC
Rated Impulse Withstand Voltage (U_{imp}):	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U_i):	690 V
Rated Operational Current AC-15 (I_e):	(120 V) 3 A (240 V) 2 A (24 V) 3 A (380 / 400 V) 0.5 A
Rated Operational Current DC-13 (I_e):	(125 V) 0.55 A (24 V) 2.5 A (250 V) 0.27 A
Rated Operational Voltage:	400 V AC 250 V DC Main Circuit 400 V AC
Recommended Screw Driver:	Pozidriv 2
RoHS Date:	0066
RoHS Information:	1SAD938507-0037 1SAD938514-0003
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	HK-20 Aux.-contact 2NO
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Suitable For:	MS325 MO325
Suitable for Product Class:	Manual Motor Starter
Tightening Torque:	Auxiliary Circuit 0.8 ... 1.0 N·m
Tightening Torque UL/CSA:	Auxiliary Circuit 7 in·lb
UL Certificate:	1SAA918002-1601
UNSPSC:	39121500
Wire Stripping Length:	Auxiliary Circuit 8 mm
cUL Certificate:	1SAA918002-1701
eClass:	7.0 27371302

