Eaton PSS25E

Catalog Number: PSS25E

Power Supply Switcher, IP20 enclosure, 20-14 AWG wire size, 1A rated operational current, 25W, Single-phase, 110-240V input voltage, 24 Vdc output voltage, 0.45A input current, 35A inrush current, 47-63 Hz, TS35 rail or chassis mount

General specifications



Product Name Catalog Number

Eaton PSG general purpose power PSS25E

supply

UPC

782113491455

Product Length/Depth Product Height

4.49 in 4.49 in

Product Width Product Weight

1.97 in 0.73 lb

Warranty Compliances

Eaton Selling Policy 25-000, one (1) year CE Marked

from the date of installation of the

Product or eighteen (18) months from the date of shipment of the Product,
whichever occurs first.

Certifications
F47 Certified
CSA Certified

UL 508

Catalog Notes

Recommended: leave 4 in free space on venting sides



Product specifications

Special features

Convection cooling, finger-safe cover, short-circuit protection, auto restart

Series

PSS

Phase

Single-phase

Operating temperature - min

-5 °C

Power consumption

25 W

Input voltage

110-240 Vac

Operating temperature - max

50 °C

Frequency rating

47-63 Hz

Mounting Method

TS35 rail or chassis

Enclosure

IP20

Output voltage

24 V

Rated operational current

6.8 A surge

1 A

0.45 A input

35 A inrush

Resources

Catalogs

Eaton's Volume 7—Logic Control, Operator Interface and Connectivity

Installation instructions

Instructions for Installing 10 and 25 Watt, 24v DC Power Supplies

Multimedia

How to size and select a Power Supply

Specifications and datasheets

Eaton Specification Sheet - PSS25E



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia