



Datasheet

Art.No. 92.060.3053.1

Distributor GST18I6 2P1T V SWPB

gesis® T-connector GST18i6; 6 pole; 1 input, 2 outputs; central locking, removable on one side; can be strung together directly; 250 V / 20 A; colour of coding: black/pastel blue



Art.No.	92.060.3053.1
EAN	4049088308352
Order unit	1 pieces

Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Yes
Lockable	Yes
Color of coding/ contact carrier	Pastel blue/black
Marking of poles	3, 2, 1, N, PE, L

Model

Number of inputs	1
Number of outputs	2
Type of fastening	No
Degree of protection (IP)	IP20
Type of distributor	T-Distributor

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C





Dimensions

Length	57.5 mm
Width	56.4 mm
Height	40.9 mm

Classification

ECLASS 8.1	27440603: Compact distributor for plug-in building installation	
ETIM 5.0	EC002567: Compact distributor for plug-in building installation	
ETIM 4.0	EC002567: Compact distributor for plug-in building installation	

Accessories

Art.No.:	Type:	Description
05.564.5353.0	Cover cap GST18I3/4/5 SW	Cover piece 12 pole black for female parts GST18i3-6
05.564.5353.2	Cover cap GST18I3/4/5 WS	Cover piece 12 pole white for female parts GST18i3-6
06.562.0753.1	Safety clip GST18I6 SW	gesis® locking clip for the flat GST18i6-system. To lock flying connections and distributors or PCB-parts with flat connectors. Colour: Black.





Drawings

