

E1N/MS12503pFHRnew



E1N/MS 1250 3p F HR new



General Information

| | |
|-----------------------|---|
| Extended Product Type | E1N/MS12503pFHRnew |
| Product ID | 1SDA058937R1 |
| EAN | 8015644612962 |
| Catalog Description | E1N/MS 1250 3p F HR new |
| Long Description | SACE EMAX C.BREAKER SWITCH-DISCONNECTOR E1N/MS 1250A THREE-POLE FIXED WITH TERMINALES REAR HORIZONTAL NEW |

Ordering

| | |
|------------------------|---------------|
| EAN | 8015644612962 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

Dimensions

| | |
|----------------------------|--------|
| Product Net Width | 296 mm |
| Product Net Height | 418 mm |
| Product Net Depth / Length | 302 mm |
| Product Net Weight | 40 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 515 mm |
| Package Level 1 Height | 600 mm |
| Package Level 1 Depth / Length | 515 mm |
| Package Level 1 Gross Weight | 50 kg |
| Package Level 1 EAN | 8015644609139 |

Additional Information

| | |
|-----------------------|-----------------------------------|
| Current Type | AC |
| Electrical Durability | 10000 cycle 30 cycles per hour |
| Mechanical Durability | 25000 cycle 60 cycles per hour |

| | |
|---|--|
| Number of Poles | 3 |
| Power Loss | 150 W |
| Product Main Type | SACE Emax |
| Product Name | Switch Disconnecter |
| Product Type | Switch-disconnector |
| Rated Current (I_n) | 1250 A |
| Rated Voltage (U_r) | 690 V |
| Rated Impulse Withstand Voltage (U_{imp}) | 12 kV |
| Rated Insulation Voltage (U_i) | 1000 V |
| Rated Operational Current (I_e) | 1250 A |
| Rated Operational Voltage | 690 V AC 250 V DC |
| Rated Short-time Withstand Current (I_{cw}) | for 1 s 50 kA for 3 s 36 kA |
| Rated Uninterrupted Current (I_u) | 1250 A |
| Standards | IEC |
| Sub-type | E1 |
| Terminal Connection Type | Fixed Circuit-Breakers Rear flat Horizontal |
| Version | F |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC200006D0209 |
| Declaration of Conformity - CE | 1SDL000165R0013 |
| Environmental Information | 1SDL000142R0 |
| Instructions and Manuals | 1SDH000460R0002 |

Classifications

| | |
|----------------------------|---|
| ETIM 4 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 5 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 6 | EC000216 - Switch disconnector |
| Object Classification Code | Q |
| UNSPSC | 39120000 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

