



### Main

Range	Linergy
Product name	Linergy TB
Product or component type	PE conductor flat bar
Accessory / separate part category	Earthing accessory
Quantity per set	Set of 1

### Complementary

Installation direction	Horizontal Vertical
Installation description	Cubicle
[Ie] rated operational current	600 A
[Icw] rated short-time withstand current	40 kA (1 s) for 3 supports (vertical position) 40 kA (1 s) (horizontal position)
Busbar cross section	50 x 5 mm
Length	1675 mm
Net weight	3.64 kg
Type of busbar connection	Ø 10 mm drilled hole
Support thickness	5 mm

### Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASEFA

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant

#### EU RoHS Declaration

Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

#### Contractual warranty

Warranty	18 months
----------	-----------