



018F7361 🗷

Solenoid coil, BB115AS, DIN Spade, 115 V

Electrical connection: DIN Spade, Supply voltage [V] AC: 115, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP00, Packing format: Multi pack

PRODUCT DETAILS

Gross weight	0.27 kg
Net weight	0.25 kg
EAN	5702428027359
Actuator size	13.5 mm
Ambient temperature range [°C]	80 ℃
[Max]	
Ambient temperature range [°C]	-40 °C
[Min]	
Ambient temperature range [°F]	176 °F
[Max]	
Ambient temperature range [°F]	-40 °F
[Min]	
Coil connection	DIN Spade
Coil design standard	VDE 0580
Coil fastening	Clip-on
Coil winding insulation class	Class H to IEC 85
Colour	Blue
Compliance	EN 60730-1
Duty rating	Continuous
Electrical connection	DIN Spade
Electrical connection size	6.3 mm x 0.8 mm
Electrical connection standard	EN175301-803
Electrical connector	3 x spades
Enclosure rating IP	IP00
Frequency [Hz]	50 Hz
Packing format	Multi pack
Parts Program name	EV210B
	EV212B
	EV220B 15 - 50
	EV220B 6 - 22
	EV220B 65 - 100
	EV222B
	EV250B
	EV251B
	EV310B
	EV224B
Power consumption 50Hz [VA]	19 VA
Power consumption [W] 50Hz	11 W
Product accessories	Solenoid coil accessories



PRODUCT DETAILS

Product group	Solenoid valves	
Product name	Solenoid coil	
Quantity per packing format	50 pc	
Rel. Humidity [% RH] [Max]	97 %	
Rel. Humidity [% RH] [Min]	0 %	
Rel. Humidity conditions	Non-condensation	
Serviceable	No	
Spare part number	018F7361	
Supply voltage 50Hz Max [V]	115 V	
Supply voltage [V] AC	115 V	
Туре	BB115AS	
Type designation	BB115AS	

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Spare Parts



016D3330 [™]

Solenoid valve, EV220B, Flange, 2 1/2 in, NBR, NC

Body material: Cast iron, Operation: Servo-operated (piston), Number of ways: 2/2



016D3331 🗷

Solenoid valve, EV220B, Flange, 3 in, NBR, NC

Body material: Cast iron, Operation: Servo-operated (piston), Number of ways: 2/2



032H8041 ¹²

Solenoid valve, EV210A, G, 1/4, FKM, NC

Body material: Stainless steel, Operation: Direct-operated, Number of ways: 2/2



032U1200 🗷

Solenoid valve, EV210B, G, 1/8, NBR, NC

Approval: DNVGL-CG-0339; GL, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U145802 🗷

Solenoid valve, EV210B, G, 1/8, FKM, NC

 $Approval: CE; DNVGL-CG-0339, Body\ material: Brass, Operation: Direct-operated, Number\ of\ ways: 2/2$



032U145831 🗷

Solenoid valve, EV210B, G, 1/8, FKM, NC

Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store 🗷





032U147002 ¹²

Solenoid valve, EV210B, G, 1/4, FKM, NC

Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U147016 12

Solenoid valve, EV210B, G, 1/4, FKM, NC

Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U147031 12

Solenoid valve, EV210B, G, 1/4, FKM, NC

Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U148002 ¹²

Solenoid valve, EV210B, G, 3/8, FKM, NC

Approval: CE, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U148016 ¹²

Solenoid valve, EV210B, G, 3/8, FKM, NC

Approval: CE, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U148031 ¹²

Solenoid valve, EV210B, G, 3/8, FKM, NC

Approval: CE, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3601 2

Solenoid valve, EV210B, G, 1/4, FKM, NC

Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3605 🗷

Solenoid valve, EV210B, G, 3/8, EPDM, NC

Approval: ACS, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3607 ¹²

Solenoid valve, EV210B, G, 3/8, EPDM, NC

Approval: ACS; DNVGL-CG-0339; GL, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3615 @

Solenoid valve, EV210B, G, 1/2, EPDM, NC

Body material: Brass, Operation: Direct-operated, Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store





032U3616 12

Solenoid valve, EV210B, G, 1/2, FKM, NC

Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3617 🗷

Solenoid valve, EV210B, G, 1/2, EPDM, NC

Approval: ACS; DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3619 ¹²

Solenoid valve, EV210B, G, 1/2, EPDM, NC

Body material: DZR brass, Operation: Direct-operated, Number of ways: 2/2



032U3621 @

Solenoid valve, EV210B, G, 3/4, EPDM, NC

Body material: DZR brass, Operation: Direct-operated, Number of ways: 2/2



032U3623 🗷

Solenoid valve, EV210B, G, 1, EPDM, NC

Body material: DZR brass, Operation: Direct-operated, Number of ways: 2/2



032U3630 🗷

Solenoid valve, EV210B, G, 1/8, EPDM, NO

Approval: ACS; DNVGL-CG-0339; PZH, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3632 🗷

Solenoid valve, EV210B, G, 1/8, EPDM, NO

Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3633 ¹²

Solenoid valve, EV210B, G, 1/8, FKM, NO

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3634 ¹²

Solenoid valve, EV210B, G, 1/8, EPDM, NO

Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3635 🗷

Solenoid valve, EV210B, G, 1/8, FKM, NO

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store





032U3636 🗷

Solenoid valve, EV210B, G, 1/4, EPDM, NO

Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3637 🗷

Solenoid valve, EV210B, G, 1/4, FKM, NO

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3638 🗷

Solenoid valve, EV210B, G, 1/4, EPDM, NO

Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3640 🗷

Solenoid valve, EV210B, G, 1/4, EPDM, NO

Approval: ACS, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3641 ¹²

Solenoid valve, EV210B, G, 1/4, FKM, NO

Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U3642 ¹²

Solenoid valve, EV210B, G, 3/8, EPDM, NC

Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U5352 🗷

Solenoid valve, EV250B, G, 1/2, EPDM, NO

Approval: ACS; DNVGL-CG-0339; GL; PZH; SINTEF, Body material: DZR brass, Operation: Assisted lift operated, Number of ways: 2/2



032U5701 🗷

Solenoid valve, EV210B, G, 1/8, EPDM, NC

Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U5702 🗷

Solenoid valve, EV210B, G, 1/8, FKM, NC

 $Approval: DNVGL-CG-0339, Body\ material: Brass, Operation: Direct-operated, Number\ of\ ways: 2/2$

For more information, please use this link to visit the product page on Danfoss Product Store 🗷





032U5705 🗷

Solenoid valve, EV210B, G, 1/8, EPDM, NC

Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U5706 2

Solenoid valve, EV210B, G, 1/8, FKM, NC

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U5707 🗷

Solenoid valve, EV210B, G, 1/4, EPDM, NC

Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U5709 🗷

Solenoid valve, EV210B, G, 1/4, EPDM, NC

Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



032U5815 🗷

Solenoid valve, EV220B, G, 1/2, EPDM, NC

Approval: PZH; SINTEF; WRAS, Body material: DZR brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U5820 [™]

Solenoid valve, EV220B, G, 3/4, EPDM, NC

Approval: PZH; SINTEF; WRAS, Body material: DZR brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U5832 🗷

Solenoid valve, EV220B, G, 1 1/4, EPDM, NC

Approval: CE; PZH; SINTEF; WRAS, Body material: DZR brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U5840 ¹²

Solenoid valve, EV220B, G, 1 1/2, EPDM, NC

Approval: CE; PZH; SINTEF, Body material: DZR brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U5850 🗷

Solenoid valve, EV220B, G, 2, EPDM, NC

Approval: CE; PZH; SINTEF, Body material: DZR brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store





032U7170 🗷

Solenoid valve, EV220B, G, 1/2, NBR, NC

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U7171 🗷

Solenoid valve, EV220B, G, 3/4, NBR, NC

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U7172 🗷

Solenoid valve, EV220B, G, 1, NBR, NC

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U7173 🗷

Solenoid valve, EV220B, G, 1 1/4, NBR, NC

Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U7174 @

Solenoid valve, EV220B, G, 1 1/2, NBR, NC

Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U7175 🗷

Solenoid valve, EV220B, G, 2, NBR, NC

Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U7180 🗷

Solenoid valve, EV220B, G, 1/2, NBR, NO

Approval: DNVGL-CG-0339; EAC; LLC CDC EURO-TYSK; UL, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U7181 🗹

Solenoid valve, EV220B, G, 3/4, NBR, NO

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U7182 🗷

Solenoid valve, EV220B, G, 1, NBR, NO

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store 🗅





032U7183 🗷

Solenoid valve, EV220B, G, 1 1/4, NBR, NO

Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U7184 2

Solenoid valve, EV220B, G, 1 1/2, NBR, NO

Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U7185 🗷

Solenoid valve, EV220B, G, 2, NBR, NO

Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8360 @

Solenoid valve, EV224B, G, 1/2, NBR, NC

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8361 ¹²

Solenoid valve, EV224B, G, 1/2, NBR, NO

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8362 ¹²

Solenoid valve, EV224B, G, 3/4, NBR, NC

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8363 🗷

Solenoid valve, EV224B, G, 3/4, NBR, NO

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8364 ¹²

Solenoid valve, EV224B, G, 1, NBR, NC

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8365 🗷

Solenoid valve, EV224B, G, 1, NBR, NO

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store 🗅





032U8500 🗷

Solenoid valve, EV220B, G, 1/2, EPDM, NC

Approval: ACS; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8501 🗷

Solenoid valve, EV220B, G, 3/4, EPDM, NC

Approval: ACS; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8502 🗷

Solenoid valve, EV220B, G, 1, EPDM, NC

Approval: ACS; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8503 🗷

Solenoid valve, EV220B, G, 1 1/4, EPDM, NC

Approval: ACS; CE; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8504 ¹²

Solenoid valve, EV220B, G, 1 1/2, EPDM, NC

Approval: ACS; CE; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8505 ¹²

Solenoid valve, EV220B, G, 2, EPDM, NC

Approval: ACS; CE; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8506 @

Solenoid valve, EV220B, G, 1/2, FKM, NC

Approval: DNV; EAC; UL, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8507 🗹

Solenoid valve, EV220B, G, 3/4, FKM, NC

Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8508 🗷

Solenoid valve, EV220B, G, 1, FKM, NC

Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2

For more information, please use this link to visit the product page on Danfoss Product Store





032U8509 🗷

Solenoid valve, EV220B, G, 1 1/4, FKM, NC

Approval: CE; PED, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8510 🗷

Solenoid valve, EV220B, G, 1 1/2, FKM, NC

Approval: CE; PED, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



032U8511 🗷

Solenoid valve, EV220B, G, 2, FKM, NC

Approval: CE; PED, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2