



R12-110-230V



R12-100-/200-/110-/020-



1- and 2-pole 16 A/250 V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.

1 module = 18 mm wide, 55 mm deep.

100% time on. Control power demand 1.9 W.

Contacts: 1 NO, 2 NO, 1 NO + 1 NC, 2 NC (closed-circuit current relay, 230 V only).

Contact gap 3mm.

Contact/contact test voltage 2000 V and control connections/contact test voltage 4000 V.

25 A devices XR12, page 19-4. Retrofittable auxiliary contact KM12, page 18-3.

The pin-compatible ER12DX-UC, ER12-200-UC and ER12-110-UC electronic switching relays can also be used.

The universal control voltage UC covers the voltage ranges of 8 to 253 V AC at 50-60 Hz and 10 to 230 V DC.

Technical data page 19-5.

R12-100-12V	1 NO 16 A	EAN 4010312200421	
R12-100-230V	1 NO 16 A	EAN 4010312200445	
R12-100-8V, 24V, 12V DC, 24V DC	1 NO 16 A		
R12-200-12V	2 NO 16 A	EAN 4010312200506	
R12-200-230V	2 NO 16 A	EAN 4010312200520	
R12-200-8V, 24V, 12V DC, 24V DC	2 NO 16 A		
R12-110-12V	1 NO + 1 NC 16 A	EAN 4010312200469	
R12-110-230V	1 NO + 1 NC 16 A	EAN 4010312200483	
R12-110-8V, 24V, 12V DC, 24V DC	1 NO + 1 NC 16 A		
R12-020-230V	2 NC 16 A	EAN 4010312201572	