

EBS 8-L / EBS 12-L Battery powered bolt cutting tool 8 mm dia. / 12 mm dia.

- ▶ For cutting cable channels, bolts and medium-hard steel wire (e.g. mild steel)
- ▶ Slim cutting head - ideal when space is critical
- ▶ Powerful 18V Lithium-Ion batteries

Characteristics

- Open cutting head, rotatable
- Electronic control and monitoring of cutting operation
- One-button operating concept for controlling all tooling functions
- Ergonomic 2-component plastic housing with soft linings for comfortable and safe one-hand operation
- Balanced centre of gravity for easy handling and effortless operations
- LED for workplace illumination
- High-performance 18 V Lithium-ions batteries with high capacity and extremely short charging time
- High-performance motors for maximum operating speed
- Energy saving function by stopping motor after successful cutting operation
- Quick motor stop for high user safety
- Automatic retraction when cut is complete
- Manual retract in case of need
- Multifunction LED for maintenance control and charging display of the battery
- Environmentally-friendly hydraulic oil, quickly biodegradable

Technical data	
Cutting range	EBS8L: max. 8 mm dia., EBS12L: max. 12 mm dia.
Cutting force	EBS8L: 15 kN, EBS12L: approx. 45 kN
Cutting time	EBS8L: approx. 1 s, EBS12L: approx. 2 s (depending on material thickness)
Number of cuts	approx. 300 for bolts 5 mm dia.
Battery voltage	18 V
Battery capacity	1.3 Ah, Li-Ion
Charging time	15 min.
Weight incl. battery	EBS8L: 1.55 kg, EBS12L: approx. 2 kg
Ambient temperature	-10°C to +40 °C

Item	Part No.
Battery powered hydraulic bolt cutting tool 8 mm dia.	EBS8L
Battery powered hydraulic bolt cutting tool 12 mm dia.	EBS12L

Scope of supply	Part No.	Page
Battery 18 V / 1.3 Ah, Li-Ion (23.4 Wh)	RAL1	398
Quick-charger for 18V Li-Ion batteries, 230 V	LGL1	400
Plastic case	KK50L	

Accessories	Part No.	Page
USB adapter	PGA1	408
18 V mains adapter for 240 V Voltage	NG2230	399
Battery 18 V / 3.0 Ah, Li-Ion (54 Wh)	RAL2	398

