

YG8U14-020UA3XLEAX

Plug connectors and cables

ACCESSORIES



YG8U14-020UA3XLEAX | Plug connectors and cables

ACCESSORIES



Ordering information

Туре	Part no.
YG8U14-020UA3XLEAX	2095589

Other models and accessories -> www.sick.com/Plug_connectors_and_cables

Detailed technical data

Technical specifications	
Accessory group	Plug connectors and cables
Accessory family	Connecting cables with female connector
Connection type head A	Female connector, M8, 4-pin, angled, A-coded
Connection type head B	Open cable ends
Locking plug connector	Screw connection
Connector material	TPU
Connector color	Black
Locking nut material	Zinc die-cast, nickel-plated
Seal material	FKM
Tightening torque	0.4 Nm
Width across flats	9
Cable	2 m, 4-wire, PUR, halogen-free
Jacket material	PUR, halogen-free
Jacket color	Black
Cable diameter	4.5 mm
Conductor cross-section	0.25 mm ²
Shielding	Unshielded
Bending radius	
Flexible use	> 10 x cable diameter
Stationary position	> 5 x cable diameter
Drag chain operation	> 10 x cable diameter
Bending cycles	5,000,000
Reference voltage	≤ 60 V DC
Rated impulse voltage	1.5 kV
Current loading	4 A
Traversing speed	3.3 m/s
Travelling distance	5 m
Acceleration	≤ 5 m/s²
Signal type	Sensor/actuator cable
Torsion force	180°/1m


YG8U14-020UA3XLEAX | Plug connectors and cables

Torsion cycles	2,000,000
Cycles per minutes	35
Application	
	Zones with oils and lubricants
	Drag chain operation
Authorizations	
	UL
UL File No.	E335179
Enclosure rating	IP65 / IP66K / IP67
Ambient operating temperature	
Flexible use	-25 °C +80 °C
Stationary position	-40 °C +80 °C
Drag chain operation	-25 °C +80 °C
Head	-25 °C +85 °C
Contamination rating	3
Insulation resistance	100 ΜΩ
Overvoltage category	III
Specific insulation resistance	30 mΩ
Classifications	

ECI@ss 6.0

27060311

Dimensional drawing (Dimensions in mm (inch))



Recommended accessories

Other models and accessories -> www.sick.com/Plug_connectors_and_cables

	Brief description	Туре	Part no.
Other mountin	accessories		
	1 piece, M8 mounting key set for SW9 with calibrated torque 0.4 \ensuremath{Nm}	TOOL-TW04M08AF09	5337207

YG8U14-020UA3XLEAX | Plug connectors and cables

ACCESSORIES

	Brief description	Туре	Part no.
Plug connect	ors and cables		
	Head A: female connector, M8, 4-pin, straight Head B: - Cable: unshielded	DOS-0804-G	6009974
	Head A: male connector, M8, 4-pin, straight Head B: - Cable: unshielded	STE-0804-G	6037323

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

